



VIBRATION ATTENUATION IN A PERIODIC ROTATING TIMOSHENKO BEAM

Maged Alaa El-Din¹ and Mohammad Tawfik¹

¹Department of Modelling & Simulation in Mechanics, German University in Cairo Cairo, Egypt <u>Maged.Mostafa@guc.edu.eg</u>

Abstract

In this study we investigate the effect of abrupt geometric discontinuities on the vibration of a Timoshenko rotating beam. The beam model is created using finite element code developed on MATLAB and stop and pass bands are identified using periodic analysis. The results are verified using published data. Numerical results indicate the effectiveness of such structure configuration on vibration attenuation.

1. INTRODUCTION AND LITERATURE SURVEY

The term "Periodic Structure" is used to describe structures that consist of a set of identical parts, cells, connected together. Periodic Structures have drawn the attention of researchers since the mid-sixties [1]-[9] because of their high ability to attenuate vibrations. Meanwhile, special attention is given to rotating beams [10]-[23] as rotating beams had wide range of engineering applications. Special attention is given to short beams where rotary inertia is taken into consideration [12], [14], [16], [20], [21] and [23]. In this paper, we will present an attempt to demonstrate the ability of geometrical periodicity of a rotating Timoshenko beam to attenuate vibrations.

2. PERIODIC ROTATING TIMOSHENKO BEAM

2.1. Displacement Field

Figure 1 shows the configuration of a periodic rotating Timoshenko cantilever beam. The beam of length (L) is connected to a rigid hub of radius (a) and rotates about the hub axis with angular velocity (Ω) . The beam itself consists of geometrically identical cells. Each cell consists of two elements as shown in Figure 2. Each element is three-node elements with four degrees of freedom per node.



Figure 1: configuration of periodic rotating Timoshenko beam



Figure 2: Typical cell configuration

Figure 3: Element degrees of freedom

The total deflection of the element as shown in Figure 3 at location (x) in z-direction can be expressed by:

$$w(x) = w_b(x) + w_s(x) \tag{1}$$

Where the subscripts b and s denotes the bending and shear deformations in xz plane respectively. Both deformations are assumed to be fifth order polynomials. They are similar in nature but different in nodal displacements. The elements degrees of freedom can be expressed by:

$$w_{i}(x) = \lfloor N_{1}(x) \ N_{2}(x) \ N_{3}(x) \ N_{4}(x) \ N_{5}(x) \ N_{6}(x) \rfloor \times \lfloor w_{i1} \ w_{i2} \ w_{i2} \ w_{i3} \ m_{i3} \rfloor^{T} = \lfloor N(x) \rfloor \{ w_{i}^{e} \}$$
(2)

Where N(x) is the shape function and w_i denotes either w_b or w_s .

2.2. Total System Energy

2.2.1. Strain energy

The system strain energy due to bending deformation and rotary inertia can be expressed as follows:

$$U = \frac{1}{2} \int_{0}^{l} \left\{ EI_{yy} \left(\frac{\partial^2 w_b}{\partial x^2} \right)^2 + GAK_s \left(\frac{\partial^2 w_s}{\partial x^2} \right)^2 \right\} dx + \frac{1}{2} \int_{0}^{l} f_c(x) \left(\frac{\partial w_b}{\partial x} + \frac{\partial w_s}{\partial x} \right)^2 dx$$
(3)

Where *E* and *G* are Young's modulus elasticity and modulus of rigidity, K_s is the shear factor, I_{yy} and *A* are the moment of inertia of cross-section and its area. $f_c(x)$ is the centrifugal force

due to rotation. The centrifugal force will be discussed in details later in this section.

2.2.2. Kinetic energy

The element kinetic energy (T) is given by:

$$T = \frac{1}{2} \int_{0}^{l} \rho I_{yy} \left(\frac{\partial^2 w_b}{\partial x \partial t} \right)^2 dx + \frac{1}{2} \int_{0}^{l} \rho A \left(\frac{\partial w_b}{\partial t} + \frac{\partial w_s}{\partial t} \right)^2 dx$$
(4)

Where ρ is the mass density.

2.2.3. External Work

The external work due to externally applied force (*F*) is given by:

$$W = \int_{0}^{l} wF dx \tag{5}$$

2.3. Hamilton's Principle

According to Hamilton's principle, the first variation of the system total energy equals to zero.

$$\partial \Pi = \int_{t_1}^{t_2} \delta(U - T - W) dt = 0$$
(6)

2.3.1. Stiffness matrix

The stiffness matrix can be derived by taking the first variation for the first integral of strain energy given by equation (3):

$$\begin{bmatrix} K \end{bmatrix} = \begin{bmatrix} [KB] & [0] \\ [0] & [KS] \end{bmatrix}, \quad \begin{bmatrix} KB \end{bmatrix} = \int_{0}^{l} EI_{yy} \{N_{xx}\} \lfloor N_{xx} \rfloor dx, \quad \begin{bmatrix} KS \end{bmatrix} = \int_{0}^{l} GAK_{s} \{N_{xx}\} \lfloor N_{xx} \rfloor dx$$
(7)

Where the subscript *x* denotes differentiation once with respect to *x*.

2.3.2. Rotation-induced stiffness matrix

The rotation-induced stiffness is the added stiffness due to centrifugal force. It can be derived by taking the first variation of the second integral of strain energy in equation (3):

$$[s] = \left[\int_{0}^{l} f_{c}(x)\{N_{x}\} N_{x} dx\right]$$
(8)

2.3.3. Mass matrix

The Mass matrix can be evaluated by taking the first variation of the kinetic energy, given by equation (4), and integrating by parts once:

$$\begin{bmatrix} M \end{bmatrix} = \begin{bmatrix} [MS] + [MB] & [MB] \\ [MB] & [MB] \end{bmatrix}, \quad [MS] = \int_{0}^{l} \rho I_{yy} \{N_x\} \lfloor N_x \rfloor dx, \quad [MB] = \int_{0}^{l} \rho A\{N\} \lfloor N \rfloor dx \tag{9}$$

2.3.4. Force vector

The vector of externally applied force can be expressed by:

$$\{F\} = \int_{0}^{l} F\{N\} dx$$
(10)

2.3.5. Element matrix equation

Finally the element matrix equations can be expressed by:

$$\begin{bmatrix} [MS] + [MB] & [MB] \\ [MB] & [MB] \end{bmatrix} \begin{bmatrix} \ddot{w}_b \\ \ddot{w}_s \end{bmatrix} + \begin{pmatrix} [KB] & [0] \\ [0] & [KS] \end{bmatrix} + \Omega^2 \begin{bmatrix} [s] & [s] \\ [s] & [s] \end{bmatrix} \begin{pmatrix} w_b \\ w_s \end{pmatrix} = \{F\}$$
(11)

2.4. Centrifugal Force

The centrifugal force induced by rotation at station (x) within the i^{th} element, measured from its left end can be expressed as follows:

$$f_c(x) = \int_{a+x_i+x}^{a+L} \rho A \zeta d\zeta$$
(12)

Where (*a*) is the hub radius, (x_i) is the distance from the beam root to the left end of the element. (ζ) is a local coordinate parallel to *x*-coordinate and is measured from the general station (*x*) as shown in Figure 1.

Since the beam is not uniform, the integration in equation (12) should be rewritten as:

$$f_c(x) = f_0(x) + f_1 \tag{13}$$

Where:

$$f_0(x) = -\rho A_i \Big((a + x_i) x + 0.5 x^2 \Big), \quad F_1 = \rho A_i \Big((a + x_i) L_i + \frac{L_i^2}{2} \Big) + \sum_{j=i+1}^n \rho A_j \Big((a + x_j) L_j + \frac{L_j^2}{2} \Big)$$
(14)

Where ρA_j , x_j and L_j is the mass per unit length of the j^{th} element, distance from root to its left end and its length respectively.

2.5. Periodic Analysis

When a wave faces abrupt change in geometry and/or material properties, part of it reflected. This reflection is destructive in some frequency bands called stop bands. In order to locate these stop bands, transfer matrix analysis is used to formulate an input/output relation between forces and displacements at left (node 1) and right (node 5) ends of the cell. See Figure 2.

$$\left[K_{dynamic}\right]\left\{w\right\}_{cell} = \left\{F\right\}_{cell}, \quad \left[K_{dynamic}\right] = \left(K + \Omega^2 S - \omega^2 M\right)$$
(15)

By condensing the internal nodes, the above relation can be rewritten as:

$$\begin{bmatrix} K_{11} & K_{12} \\ K_{21} & K_{22} \end{bmatrix} \begin{cases} w_1 \\ w_5 \end{cases} = \begin{cases} F_1 \\ F_5 \end{cases}$$
(16)

Where w_1 , F_1 , w_5 and F_5 are the displacements and forces at nodes 1 and 5 respectively. Rewriting the above equation in form of input/output relation [9]:

$$\begin{bmatrix} T_{11} & T_{12} \\ T_{21} & T_{22} \end{bmatrix} \begin{bmatrix} w_1 \\ F_1 \end{bmatrix} = \begin{bmatrix} w_5 \\ F_5 \end{bmatrix}$$
(17)

Assume:

$$\begin{cases} w_5 \\ F_5 \end{cases} = e^{\mu} \begin{cases} w_1 \\ -F_1 \end{cases}$$
 (18)

Substituting equation (18) into (17):

$$\begin{bmatrix} T \end{bmatrix} \begin{cases} w_1 \\ F_1 \end{bmatrix} = e^{\mu} \begin{cases} w_1 \\ F_1 \end{cases}, \begin{bmatrix} T \end{bmatrix} = \begin{bmatrix} T_{11} & T_{12} \\ -T_{21} & -T_{22} \end{bmatrix}$$
(19)

The above eigenvalue problem can be solved for propagation factor μ , which is, generally, a complex number its real part represents the boundaries of the pass/stop bands, and the imaginary part gives the attenuation value. Since the transfer matrix *[T]* varies from one cell to another, the location of stop bands will vary to. Thus average will be taken for all cells.

3. NUMERICAL RESULTS

The finite element model described above has been developed on MATLAB 7.0. Herein after,

some numerical results are listed for comparison purposes. However, no test data are published for rotating periodic Timoshenko beam. Thus, comparison will be accomplished on two steps. The first, comparing the natural frequencies generated by this model for uniform beam with literature [10]. The second, comparing results for periodic Timoshenko beam with published Euler-Bernoulli periodic beam [8]

3.1. Uniform Rotating Timoshenko Beam

Stafford and Giurgiutiu [10] derived semi-analytical methods to evaluate natural frequencies of rotating Timoshenko beam. Table 1 contains comparison between the current finite element model and reference [10]. These non-dimensional natural frequencies are calculated for beam with characteristics stated in Table 2. From Table 1, the finite element model showed good agreement.

Mode	Exact (Ref. [10])	Current Model
1	6.8509	6.9301
2	19.6787	19.839
3	38.5758	38.679
4	56.295	55.229

Table 1: Non-dimensional natural frequencies of uniform rotating Timoshenko beam

L	EI	ho I	E/G	<i>v</i> Passion Ratio	<i>L/R</i> (length-to-radius of gyration)	$\sqrt{\alpha} = \sqrt{\frac{\rho A L^2}{EI}} \Omega$ Non-dim rotational

10

6

0.3

Table 2: Characteristics of uniform rotating Timoshenko beam

3.2. Periodic Rotating Timoshenko Beam

2.6

For the sake of comparison, reference [8] is utilized where periodic rotating Euler Bernoulli beam had been analyzed both numerically and experimentally. The parameters of the selected beam can be found in Table 3. Figure 4 shows the tip response of the selected beam in comparison with a similar plain beam of thickness 1 mm subjected to rotation speed or 5 revolutions per second (300 rpm). It is clear from the figure that tip response is attenuated when average attenuation factor is nonzero. The current model showed good agreement with data published in reference [8].

Material		Beam dim. (cm)			Thin part		Thick Part			
(Aluminum)										
E	v	ρ	Hub	Length	width	Cell	Length	Thickness	Length	Thickness
GPa		Kg/m^3	radius			Length	cm	mm	cm	mm
71	0.3	2700	5	45	3.6	11.25	6.25	1	5	3

Table 3: Characteristics of periodic rotating beam

Figure 5 shows the same beam when it is subjected to rotation speed of 3000rpm. From the figure it is noticed the attenuation factor is getting wider with less attenuation value.



Figure 4: Frequency response of periodic rotating Timoshenko beam (5 rev/sec)



Figure 5: Frequency response of periodic rotating Timoshenko beam (50 rev/sec)

4. CONCLUSIONS

In this study, a finite element model for a periodic rotating Timoshenko beam has been presented. From the results shown, the model proved that geometrical periodicity has high ability to attenuate vibrations in some frequency bands showing good agreement with published data. Also, increasing the rotation speed broaden the stop bands with less attenuation value. Proper design can achieve high attenuation value for some target frequency bands. The selected 3-node 4 DOF/node element showed good results.

REFERENCES

- [1] D. Mead, "Wave propagation in continuous period structures: research contributions from Southampton, 1964-1995" *Journal of Sound and Vibration* **190**, 495-524 (1996).
- [2] D. Mead and Y. Yaman, "The response of infinite periodic beams to point harmonic force: A flexural wave analysis", *Journal of Sound and Vibration* 144, 507-530 (1991).
- [3] D. Mead, R. G. White and X. M. Zhang, "Power transmission in periodically supported infinite beam excited at a single point", *Journal of Sound and Vibrations* 169, 558-561 (1994).
- [4] H. Ouyang, F. W. Williams and D. Kennedy, "Letters to the editor: A general method for analyzing wave propagation along longitudinally periodic structures", *Journal of Sound and Vibration* 177, 277-281 (1994).
- [5] R. S. Langley, "On the forced response of one-dimensional periodic structures: Vibration localization by damping", *Journal of Sound and Vibration* **178**, 411-428 (1994).
- [6] S. D. Lust, P. P. Friedmann, and O. O. Bendiksen, "Free and forced response of multi-span beams and multi-bay trusses with localized modes", *Journal of Sound and Vibration* **180**, 313-332 (1995).
- [7] M. A. Heckl, "Coupled waves on a periodically supported Timoshenko beam", *Journal of Sound and Vibration* **252**, 849-882 (2002).
- [8] M. Tawfik, J. Chung and A. Baz, "Wave Attenuation in Periodic Helicopter Blade", proceedings of the Fifth Jordan International Mechanical Engineering Conference, 26-28 April 2004, Amman, Jordan.
- [9] M. Alaa El-Din and M. Tawfik "Vibration characteristics of rotating beams with periodically distributed piezoelectric dampers", *Proceedings of the Thirteenth International Congress on Sound and Vibration* (ICSV13), 2-6 July 2006, Vienna, Austria.
- [10] R. D. Stafford and V. Giurgiutiu, "Semi-analytical methods for rotating Timoshenko beams", *International Journal of Mechanical Engineering* 17, 719-272 (1975).
- [11] K. M. Udupa, and T. K. Varadan, "Hierarchical finite element method for rotating beams", *Journal of Sound and Vibration* 138, 447-456 (1990).
- [12] S. Mulmule, G. Singh and G. Venkateswara Rao, "Flexural vibration of rotating tapered Timoshenko beams", *Journal of Sound and Vibration* 160, 372-377 (1993).
- [13] S. Y. Lee and Y. H. Kuo, "Bending frequency of a rotating Timoshenko beam with general elastically restrained root", *Journal of Sound and Vibration* **162**, 243-250 (1993).
- [14] H. Du, M. K. Lim and K. M. Liew, "A power series solution for vibration of a rotating Timoshenko beam", *Journal of Sound and Vibration* 175, 505-523 (1994).
- [15] H. H. Yoo, R. R. Ryan, and R. A. Scott, "Dynamics of flexible beams undergoing overall motions", *Journal of Sound and Vibration* 181, 261-278 (1995).
- [16] V. T. Nagaraj, "Approximate formula for the frequencies of a rotating Timoshenko beam", *Journal of Aircraft* **33**, 637-639 (1996).
- [17] H.H. Yoo and S. H. Shin, "Vibration analysis of rotating cantilever beams", *Journal of Sound and Vibration* **212**, 807-828 (1998).
- [18] S. M. Hashemi and M. J. Richard, "A new dynamic finite element (DFE) formulation for lateral free vibrations of Euler-Bernoulli spinning beams using trigonometric shape functions", *Journal of Sound and Vibration* 220, 601-624 (1999).
- [19] J. R. Banerjee, "Free vibration of centrifugally stiffened uniform and tapered beams using the dynamic stiffness method", *Journal of Sound and Vibration* 233, 857-875 (2000).
- [20] S. C. Lin and K. M. Hsiao, "Vibration analysis of a rotating Timoshenko beam", *Journal of Sound and Vibration* 240, 303-322 (2001).
- [21] S. Rao and R. Gupta, "Finite element vibration analysis of rotating Timoshenko beams", *Journal of Sound and Vibration* **242**, 103-124 (2001).
- [22] J. Chung and H. H. Yoo, "Dynamic analysis of a rotating cantilever beam by using the finite element method", *Journal of Sound and Vibration* 249, 147-164 (2002).
- [23] B. Yardimoglu and Y. Yildirim, "Finite element model for vibration analysis of pre-twisted Timoshenko beam", *Journal of Sound and Vibrations* 273, 741-754 (2004).